OFFGRID OUTBACK

DENHAM **KING ISLAND** DALY RIVER **ROTTNEST ISLAND** COOBER PEDY james.hamilton@utas.edu.au

and the rest ..

UNIVERSITY of TASMANIA

OFFGRID OUTBACK

H MER International MICROGRID Conference 8th Annual #HIMC2020



BEWARE UNFENCED ROAD

FOR NEXT 1500km

The Infamous Five

Denham	King Is.	Daly River	Rottnest Is.	Cobber Pedy	
West Australia	Tasmania	Northern Territory	West Australia	South Australia	
Population 500	Population 1700	Population 127	Population 300	Population 1700	
Annual Load GWh 5	Annual Load GWh 12	Annual Load GWh 3	Annual Load GWh 5	Annual Load GWh 12	
RE% 45%	RE% 65%	RE% 50%	RE% 45%	RE% 70%	
Commissioned 1997	Commissioned 1998	Commissioned 2016	Commissioned 2017	Commissioned 2018	

and the rest ...

Project	Annual Load MWh	Thermal MW	Wind MW	Solar MW	Storage MW/MWh	RE %	Year
Agnew	240,000	32	18	4	13, 4.0	60%	2020
Coober Pedy	11,500	3.92	4	1	1.5, 0.49	70%	2018
Coral bay	3,000	2.24	0.675			45%	2007
Daly River	3,000	1.82	0	1	0.8, 2.0	50%	2016
Denham	5,500	2.62	1.02			35%	1997
Doomadgee	5,700	2.5	0	0.264		8%	2013
Flinders Island	6,700	3	1.2	0.7	0.75, 0.3	55%	2016
Granny Smith	180,000	24.2	0	8	2.0, 1.0	10%	2020
Hopetoun	5,800	5.18	1.2			40%	2005
Kalbarri	12,000	4	1.6	1.1	5.0, 4.5	40%	2020
King Island	12,000	6	2.25	0.9	3.0, 1.6 (+2 FW)	60%	1998-2014
Lord Howe Island	2,300	1.325	0	1.2	1.0, 3.2	60%	2020
Mackerel Island	1,000	0.44	0	0.32	0.6, 0.6	92%	2014
Marble Bar	2,365	1.28	0	0.3	(0.5 FW)	30%	2010
Nullagine	1,200	0.96	0	0.2		34%	2010
Onslow	8,200	8	0	1	3.0, 2.0	50%	2019
Port Gregory	26,000	9	2.5	1	2.0, 0.5	70%	2020
Rottnest Island	5,000	2.1	1.2	0.6		45%	1982/2006/2017
Thursday Island	18,500	9	0.45			5%	1997
Windorah	1,090	0.75	0	.13 (thermal)		16%	2009

Denham, Western Australia

First variable speed inverter wind turbine in Australia
Enercon E30 (Total 230kW) & Powercorp PSAC 20% wind penetration

•Two additional E30 turbines (Total 690kW) •30-35% wind penetration

1997

1998

2001

2007

2021

•Plans for 2 x 300kVA flywheels to run diesel off abandoned after not meeting technical specification.

•Low load diesel developed for MTU Series 60 engines •40-45% wind penetration

Enercon E 33 (Total 1020kW) added.Comparatively, 2940kW of diesel generation onsite.

•Renewable hydrogen production and generation pilot

Source: Chris Dowe, Synergy, 2018


HMER InternationalREP: 45%MICROGRID Conference | 8th Annual | #HIMC2020





1009





Severe constraint on wind energy Allows very high wind penetration

King Island, Tasmania

Population: 1600 Load: 12,000 MWh REP: 60%




Daly River, Northern Territory

Population: 127 Load: 3,000 MWh REP: 50%

- A. Morning load, diesel on, BESS empty.
- B. PV coming online
- C. Diesel at low load with BESS charging
- D. Bess charging & performing isochrono control
- E. Excess solar charges BESS
- F. Solar PV spill as BESS full
- G. BESS discharge into evening.
- H. Diesel off until BESS empty
- I. Diesel on
- J. Diesel supply night time load





Source: Power and Water Corporation, Daly River Lessons Learnt, 2019

Rottnest Island, West Aus.


Population: 300 Load: 5,000 MWh REP: 45%

http://www.rottnestisland.com/the-island/travel-tools-and-tips/apps



Coober Pedy, South Australia

Population: 1790 Load: 11,500 MWh REP: 70%



HMER International MICROGRID Conference 8th Annual #HIMC2020

Knowledge Bank

- https://www.hydro.com.au/clean-energy/hybrid-energysolutions/success-stories
- https://www.powerwater.com.au/about/projects/currentprojects/solar-energy-transformation-program
- https://edlenergy.com/project/coober-pedy/

james.hamilton@utas.edu.au

SOLATE June 2022 POWER Jabiru, Aus. YSTEM 2099

www.ipsconnect.org